

XPS MULTI 20

Description

XPS MULTI 20 is a rigid thermal insulation board made of extruded polystyrene (XPS) foam produced according to climate-friendly CO₂ technology.

XPS MULTI 20 is mainly used as thermal insulation including floors and walls.

Packing & Storage

	XPS MULTI 20
Thickness (mm)	20
Boards/pack	21
m ² /pack	15,75
Packs/pallet	12
m ² /pallet ⁽¹⁾	189

(1) In addition to the default pallet, there is also a "jumbo" pack, composed of 2x2 pallets.

Store the insulation boards on a flat surface, keep dry and protected from sunlight.

Characteristics

	XPS MULTI 20
Thermal conductivity (W/(m.K))	0,034
Length (mm)	1250 ± 8
Width (mm)	600 ± 8
Density (kg/m ³)	30 ± 15 %
Edge profile	smooth edge
Surface	rough
Compressive strength at 10% deformation (kPa) (EN 826)	≥ 250
Thermal resistance (m ² .K/W)	0,60

Installation

Always consult the local regulations and installation guidelines of the manufacturer.
After installation the insulation boards must be protected against weather conditions.

Certifications

Acermi 07/107/486

SOPREMA reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order.

Special indications

Health, Environment and Safety

The product does not contain any substance which is likely to be detrimental to health or to environment and complies with generally admitted Health and Safety Requirements.

For more information, please refer to the relevant safety data sheet.

Quality-, Environment- and Safety Management

SOPREMA has always attached the highest importance to the quality of the products, the environment and safety.

For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.

A blue ink signature of Marnix Derks.

Marnix DERKS
Technical Director
Grobbendonk, 20/06/2017

SOPREMA reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order.