

SOPRADERE QUICK

SOPRADERE QUICK is a ready-to-use cold applied fast drying bitumen emulsion primer composed of bitumen, volatile solvents and adhesive additives.

User application

SOPRADERE QUICK is used as cold-applied primer on concrete, degreased metal or wood-based substrate, to increase the adhesion of bituminous waterproofing membranes hot bonded or torched-on, in compliance with French Code of Practice DTU 43 (NF P 84-204).

All the applications are described in **SOPREMA**'s Technical Guidelines in force.

Composition

	SOPRADERE QUICK
Physical state	Dark homogeneous liquid, leaving a black coloured film after drying
Dry content	> 40 % of weight
Density at 20°C	about 950 kg/m ³ (± 50)
Viscosity cup n°4 at 20°C	23 to 27 °C
Flash point (ASTM D 56)	+ 24°C
Drying time on concrete	Less than 30 minutes

Packaging

	SOPRADERE QUICK
Packaging	Cans of 5 or 25 liters
Consumption	Consumption depends on the uses and the substrate. On rough and absorbent substrate (i.e concrete, wood) : - 5 L can cover about 20 m ² - 25 L can cover about 100 m ² On smooth, non absorbent substrate (i.e metal), the average consumption may be lower.
Storage	The product can be stored until 12 months at a temperature between 5°C and 35°C in closed original packaging and protected from the sun.

Installation

Before use, well homogenize **SOPRADERE QUICK**. The tools used (roll, brush, rubber squeegee) must be clean.

SOPRADERE QUICK must be applied with a brush or a roller onto dry, clean surfaces, free of all dust and non-adhesive parts (concrete, wood, metal ... previously degreased).
Let dry completely before apply the waterproofing membrane.

Cleaning tools:

Petroleum solvent (white spirit, xylene for example).

Special indications

Hygiene, health and environment:

- Flammable: keep away from flames and sparks during use.
- **SOPRADERE QUICK** contains xylene.
- Ensure that all cans, empty or full, containing flammable substances are kept at least 10 m away.
- If spray gun is used, ensure that no incompatible material is used that may create sparks.
- Close cans properly after each use.
- Do not breathe in fumes.
- Avoid the product coming in contact with eyes.
- Do not smoke while product is being used.
- Do not swallow.
- Do not throw wastes into sewers.

For further information, please refer to relevant Safety Data Sheet.

Quality control:

SOPREMA has always attached the highest importance to the quality of its products, to the respect of environment and men.

For this reason, we apply an integrated management of the Quality and Environment certified **ISO 9001** and **ISO 14001**.