

DECLARATION OF PERFORMANCE

n° PROFR005

Date : Mai, 15th 2014

1 – Unique identification code of the product-type:

PROFR005

2 – Identification of construction product, in accordance with article 11 § 4 of regulation (EU) N° 305/2011 :

PLASTIGRILLE

3 – Intended use (or uses) of the construction product :

Underlays for discontinuous roofing

4 – Name, registered trade name or registered trademark and contact address of the manufacturer, in accordance with article 11 § 5 of Regulation (EU) N° 305/2011 :

**SOPREMA SAS
14, rue de Saint-Nazaire – CS 60121
67100 STRASBOURG
www.soprema.com**

5 – Name and contact address of the authorised representative whose mandate covers the tasks specified in article 12 § 2 of Regulation (EU) N° 305/2011 :

Non applicable

6 – System (or systems) of assessment and verification of constancy of performance of the construction product as set out in Annex V of Regulation (EU) N° 305/2011 :

AVCP 3

7 – Case of the declaration of performance concerning a construction product covered by a harmonised standard :

The TSUS (Notified Body n°1301):

- **made the determination of the product-type on the basis of type testing, according to system 3**
- **issued the corresponding tests reports.**

8 – Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :

Non applicable



Roofing material solutions

DECLARATION OF PERFORMANCE

n° PROFR005

Date : Mai, 15th 2014

9 – Declared performances :

Essential characteristics	Performances	Harmonised Technical Specification
Reaction to fire	F	EN 13859-1 : 2010
Resistance to water penetration	W2	
Tensile properties :		
Tensile strength - Longitudinal - Transversal	300 ± 50 N/50 mm 250 ± 50 N/50 mm	
Elongation - Longitudinal - Transversal	23 [-5 ; +10] % 23 [-5 ; +10] %	
Resistance to tearing (Nail shank) - Longitudinal - Transversal	165 [-15 ; +50] N 155 [-5 ; +50] N	
Flexibility at low temperature (Pliability)	-40°C	
Artificial ageing behavior :		
Resistance to water penetration	W2	
Tensile strength - Longitudinal - Transversal	320 ± 50 N/50 mm 190 ± 50 N/50 mm	
Elongation - Longitudinal - Transversal	21 [-10 ; +10] % 24 [-15 ; +10] %	

10 – The performances of the product identified in points 1 and 2 are in conformity with the declared performances in point 9.

This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :

Strasbourg,
Export Technical Manager, Mr Pascal MOUGEOT-LUDIN