

# DILUANT V

# DILUANT L

## 1 PRESENTATION

**DILUANT V:** light, volatile thinner.

**DILUANT L:** heavy thinner for **ALSAN 310**, **ALSAN 400** and **ALSAN 500** waterproofing kit.

## 2 CHARACTERISTICS

	<b>DILUANT V</b>	<b>DILUANT L</b>
<b>Aspect</b>	Plain liquid	Plain liquid
<b>Density at 20°C (ASTM D1475)</b>	800 kg/m <sup>3</sup>	970 kg/m <sup>3</sup>
<b>Flash point (DIN 53 213)</b>	- 4°C	42°C
<b>Flammability</b>	Easily flammable	Flammable

## 3 PACKAGING AND CONSUMPTION

Cans: 5 kg and 10 liters.

Storage: In a cool, dry, ventilated area.

## 4 USER'S APPLICATION

For the thinning of **ALSAN 310**, **ALSAN 400** and **ALSAN 500** products and primers.  
Do not exceed 8 % of dilution.

**DILUANT V:** Light, rapid evaporating thinner. Adapted to normal atmospheric conditions (temperate climate).

**DILUANT L:** Heavy, slow evaporating thinner. Adapted to particular atmospheric conditions (high temperature, wind...). Slows down the hardening process of resins and aids the penetration of primers on porous surfaces. Cleaning material.



**SOPREMA Liquid Waterproofing Department**

14 rue de Saint-Nazaire - BP 60121 - 67025 STRASBOURG Cedex 1 - FRANCE  
Phone: +33 (0)3 88 79 84 84 - Fax: +33 (0)3 88 79 84 85  
E-mail: export@soprema.com - www.soprema.com

## 5 INSTALLATION

All the applications are described in Soprema's technical guidelines.

## 6 SPECIAL INDICATIONS

### Precautions:

- **DILUANT V**
  - **Easily flammable:** Prior to the use of a flame, ensure that all cans, empty or full, of flammable substances are at least 10 m away.
  - May irritate eyes and respiratory tracts.
- **DILUANT L**
  - Flammable: ensure that all cans, empty or full, of flammable substances are at least 10 m away.
  - Irritating to eyes

For more information, please refer to the relevant Safety data Sheet.

### Quality control:

**SOPREMA** has always attached the highest importance to Quality Control. For this reason, we operate an internationally recognized Quality System according to ISO 9001: 2008 with the system being independently monitored and certified by BSI.



**SOPREMA Liquid Waterproofing Department**

14 rue de Saint-Nazaire - BP 60121 - 67025 STRASBOURG Cedex 1 - FRANCE  
Phone: +33 (0)3 88 79 84 84 - Fax: +33 (0)3 88 79 84 85  
E-mail: export@soprema.com - www.soprema.com