

DECLARATION OF PERFORMANCE

n° MISFR007

Date : May, 5th 2014

1 – Unique identification code of the product-type:

MISFR007

2 – Identification of construction product, in accordance with article 11 § 4 of regulation (EU) N° 305/2011 :

DRAIN 2F

3 – Intended use (or uses) of the construction product :

Geotextiles for use in drainage systems (intended uses : F / F+S / D)

4 – Name, registered trade name or registered trademark and contact address of the manufacturer, in accordance with article 11 § 5 of Regulation (EU) N° 305/2011 :

**SOPREMA SAS
14, rue de Saint-Nazaire – CS 60121
67100 STRASBOURG
www.soprema.com**

5 – Name and contact address of the authorised representative whose mandate covers the tasks specified in article 12 § 2 of Regulation (EU) N° 305/2011 :

Non applicable

6 – System (or systems) of assessment and verification of constancy of performance of the construction product as set out in Annex V of Regulation (EU) N° 305/2011 :

AVCP 2+

7 – Case of the declaration of performance concerning a construction product covered by a harmonised standard :

The British Textile Technology Group (Notified Body n°0338):

- **performed the inspection of the system of Factory Production Control under system 2+**
- **issued the conformity certificates of Factory Production Control.**

8 – Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :

Non applicable

DECLARATION OF PERFORMANCE

n° MISFR007

Date : May, 5th 2014

9 – Declared performances :

Essential characteristics	Performances	Harmonised Technical Specification
Tensile properties : Tensile strength (kN / m) Longitudinal Transverse Elongation (%) Longitudinal Transverse	20 [- 2] 15,5 [-1,5] 35 [±15] 35 [±15]	EN 13252:2000 + A1:2005
Resistance to dynamic perforation (mm)	38 [+5]	
Resistance to static loading (kN)	3,3 [-0,33]	
Filtration aperture (µm)	75 [± 20]	
Water permeability (mm/s)	50 [-15]	
Flow capacity in the plan (m ² /s)	65.10⁻⁵ [-6,5.10⁻⁵]	
Dangerous substances	Complies	

Note 1 : The performances for perforation, filtration aperture and water permeability are indicated for the geotextile only before thermowelding on the grid and for only one thickness.

10 – The performances of the product identified in points 1 and 2 are in conformity with the declared performances in point 9.

This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :

**Strasbourg,
Export Technical Manager, Mr Pascal MOUGEOT-LUDIN**

