

FLAG GEOTEXTILE PP

Description

FLAG GEOTEXTILE PP is a non-woven polypropylene geotextile.

Characteristics

	FLAG GEOTEXTILE PP	
	PP 400	PP 800
Weight (UNI 8202/6)	400 g/m ² (±10%)	800 g/m ² (±10%)
Tensile strength (UNI 8639)	≥ 520 N / 5 cm	≥ 1100 N / 5 cm
Elongation (UNI 8639)	≥ 60 %	≥ 50 %
Puncture resistance (UNI 5421)	≥ 700 N	≥ 1500 N

Packaging

	FLAG GEOTEXTILE PP	
	PP 400	PP 800
Roll dimensions	70 m x 2 m	30 m x 2 m
Roll weight	56 kg	48 kg

User application

FLAG GEOTEXTILE PP is used as a separation layer or regularization layer for **FLAG** waterproofing systems.

Special indications

Hygiene, health and environment:

The product does not contain any substance likely to be detrimental to health or to environment and complies with generally admitted Health and Safety Requirements. For more information, please refer to relevant Safety Data Sheet.

Quality control:

SOPREMA has always attached the highest importance to Quality Control.

For this reason, we operate an independently monitored Quality Assurance System in compliance with **BS EN ISO 9001: 2008**, certified by **BSI Management System**.

