

FLAGON FLEXOCOL C

Description

FLAGON FLEXOCOL C is a ready-to-use, single component, polyurethane, contact adhesive for non-backed PVC waterproofing membranes.

Characteristics

Composition	polyurethane resins and solvents
Open time ⁽¹⁾	±30 min. (20 °C)
Curing time ⁽¹⁾	±60 min. (20 °C)
Consumption	±3 m ² /l
Application temperature	+5 / +30 °C
⁽¹⁾ Depending on conditions (temperature, relative humidity, ...)	

Packing & storage

Can 5 or 20 l

Minimum 6 months in original unopened packaging, stored in a dry and cool place at a temperature between +5 and +30 °C. Opened product has a limited shelf life.

Installation

The substrate and membrane must be clean, solid and free from dust and grease.

Use a roller or brush to apply the adhesive on both surfaces.

As soon as the adhesive is tacky on the touch, on both sides, roll the coated membrane onto the coated substrate.

Use a roller or by hand to press the membrane into the adhesive.

Cleaning tools:

- remove uncured product with FLAGON Solvent 6
- cured product needs to be removed mechanically

Special indications

Hygiene, Health and Environment

For more information, please refer to the relevant safety data sheet.

Quality-, Environment- and Safety Management

SOPREMA always recognises as a high level of importance the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.