

DECLARATION OF PERFORMANCE

N° WPBBE0406

Unique identification code of the product type: **SOPRAROCK GLOBAL SBS 30 TF**

Intended use(s): Reinforced bituminous sheet for roof waterproofing

Manufacturer: Soprema NV

Bouwelven 5 - 2280 Grobbendonk

Belgium

System(s) of AVCP: system 2+

Harmonised standard: EN 13707:2004 + A2:2009

0749 Notified body/ies:

Declared performances

Essential characteristics			Performances		Test standard	Harmonised standard
External fire performance (note 1)			FROOF(t	1, t2, t3, t4)	EN 13501-5	
Reaction to fire			NPD		EN 13501-1	
Watertightness		(kPa/24 h)	≥ 10		EN 1928	
Tensile strength:	longitudinal transversal	(N/50 mm) (N/50 mm)	650 450	± 20 % ± 20 %		
Elongation at maximum	n tensile strength: longitudinal transversal	(%) (%)	35 35	± 15 ± 15	EN 12311-1	
Resistance to root penetration			NPD		EN 13948	
Resistance to static loading		(kg)	NPD	and the second	EN 12730-A	
Resistance to impact		(mm)	NPD NPD		EN 12691-A EN 12691-B	EN 13707:2004 +
Resistance to tearing (r	nail shank)					A2:2009
/	longitudinal transversal	(N) (N)	170 170	± 25 % ± 25 %	EN 12310-1	
Joint properties:	peel resistance shear resistance	(N/50 mm) (N/50 mm)	160 800	± 25 % ± 25 %	EN 12316-1 EN 12317-1	
Behaviour after artificial aging					EN 1296 +	
durability UV, heat and water			NPD		EN 1297	
flow resistance at elevated temperature (°C)			100	-0/+20	EN 1110	
flexibility at low temperature (°C)			-20	± 5	EN 1109	
Flexibility at low temperature (°C)			≤ -20		EN 1109	
Dangerous substances (note 2)			note 3		- 1	

NPD = no performance determined

since external fire performance depends on the other components of the roof build-up, no performance can be given this product does not contain asbestos or tar constituents

in the absence of European harmonized test methods, verification and declaration on release and content has to be done taking into account national provisions in the place of use

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Marnix Derks, Technical Director Grobbendonk, 27/08/2020

