

## **DECLARATION OF PERFORMANCE**

**n° WPBFR102**

**Date : June, 30<sup>th</sup> 2013**

*1 – Unique identification code of the product-type:*

**WPBFR102**

*2 – Identification of construction product, in accordance with article 11 § 4 of regulation (EU) N° 305/2011 :*

**ELASTOPHENE 25**

*3 – Intended use (or uses) of the construction product :*

**Flexible sheets for waterproofing – Bitumen water vapour control layer**

*4 – Name, registered trade name or registered trademark and contact address of the manufacturer, in accordance with article 11 § 5 of Regulation (EU) N° 305/2011 :*

**SOPREMA SAS  
14, rue de Saint-Nazaire – CS 60121  
67100 STRASBOURG  
www.soprema.com**

*5 – Name and contact address of the authorised representative whose mandate covers the tasks specified in article 12 § 2 of Regulation (EU) N° 305/2011 :*

**Non applicable**

*6 – System (or systems) of assessment and verification of constancy of performance of the construction product as set out in Annex V of Regulation (EU) N° 305/2011 :*

**AVCP 3**

*7 – Case of the declaration of performance concerning a construction product covered by a harmonised standard :*

**The LNE (Notified Body n°0071):**

- **Made the determination of the product-type on the basis of type testing, according to system 3**
- **issued the corresponding tests reports.**

*8 – Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :*

**Non applicable**

# DECLARATION OF PERFORMANCE

**n° WPBFR102**

**Date : June, 30<sup>th</sup> 2013**

*9 – Declared performances :*

Essential characteristics	Performances	Harmonised Technical Specification
Reaction to fire	<b>E</b>	<b>EN 13970:2004</b>
Watertightness	<b>Conform</b>	
Tensile properties : Tensile strength L x T (N / 50 mm) Elongation L x T (%)	<b>≥ 250 x 150 2 x 2</b>	
Resistance to impact (mm)	<b>400</b>	
Shear resistance of joints (N/50 mm)	<b>≥ 150</b>	
Flexibility at low temperature	<b>-16°C</b>	
Resistance to tearing (N)	<b>≥ 50</b>	
Durability (resistance to humidity) Against artificial ageing Against chemicals	<b>Conform NPD</b>	
Properties of water vapour transmission (resistance to humidity)	<b>≥ 6,9 10<sup>4</sup></b>	
Dangerous substances (Notes 1 and 2)	<b>Complies</b>	

Note 1 : This product does not contain asbestos or tar constituents.

Note 2 : Since there is no European test method available, no performance declaration for leaching behavior can be made. It must be made according to national rules in force in the place of use.

*10 – The performances of the product identified in points 1 and 2 are in conformity with the declared performances in point 9.*

*This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 4.*

*Signed for and on behalf of the manufacturer by :*

**Strasbourg,  
Export Technical Manager, Mr Pascal MOUGEOT-LUDIN**

