



- Outstanding contact sound-insulation
- Combines high contact sound insulation properties with a high load capacity
- Versatile application under particle board flooring and parquet



Packaging

Thickness [mm]	Boards/pallet	Dimensions [mm]	m ² /pallet [m ²]	Mass/pallet [kg]	Thermal resistance (R _d) [m ² .K/W]
17	240	1100 x 600	158,4	384	0,40
22	160	1100 x 600	105,6	334	0,55
32	120	1100 x 600	97,2	362	0,80

Production: Switzerland

Characteristics

Density [kg/m ³]	135
Thermal conductivity (λ _d) (EN 13171) [W/(m.K)]	0,038
Specific heat capacity (c) [J/(kg.K)]	2100
Water vapour diffusion resistance coefficient (μ) [-]	5
Reaction to fire (EN 13501-1)	E
Dynamic stiffness [MN/m ³]	17/16 mm ≤ 50 22/21 mm ≤ 40 32/30 mm ≤ 30
Waste code according to The European Waste Catalogue (EWC)	030105; 170201; 170604
Edge profile	straight

Product description

PAVAPOR is a natural and ecological contact-sound insulation board based on wood fiber.

The high load capacity makes that the board can be used in all floor applications such as cement-bound screeds, particle board flooring and parquet.

Always consult the local regulations and installation guidelines of the manufacturer.

Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

For more information, please refer to the relevant safety data sheet.

Storage

Store the insulation boards on a flat surface, keep dry and protected from sunlight.

Stack no more than 4 pallets on top of each other.

