

FLAGON Solvent 13

Description

Is a solvent-based cleaning fluid used to prepare FLAGON TPO membranes during installation.

Characteristics

	FLAGON Solvent 13
Composition	solvents
Application temperature	+5 / +25 °C

Packing & storage

Can 5 l

Minimum 12 months in original unopened packaging, stored in a dry and cool place at a temperature between +5 and +25 °C.

Application

Use a solvent-proof and lint-free cloth.

Where required, apply liberally to remove contaminants from the FLAGON TPO waterproofing membrane. Wait for the surface to dry and the solvents evaporate prior to welding.

SOPREMA reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order.

Special indications

Health, Environment and Safety

For more information, please refer to the relevant safety data sheet.

Quality-, Environment- and Safety Management

SOPREMA has always attached the highest importance to the quality of the products, the environment and safety.

For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.



Marnix DERKS
Technical Director
Grobendonk, 30/06/2017

SOPREMA reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order.