

## SOPRADERE QUICK

### Description

Cold applied fast drying primer based on bitumen, solvents and adhesion-improving additives. Impregnation to ensure good adhesion to the substrate (concrete, metal and wood) before welding (torch-on or hot-air method) or gluing bituminous waterproofing membranes. It is also suitable on old/weathered bituminous waterproofing membranes with a slate or granulate finish.

### Characteristics

Composition	bitumen, solvents and adhesion-improving additives
Curing time *	30 min.
Consumption (l/m <sup>2</sup> )	0,15 - 0,25
Application temperature (°C)	min. +5

\* Depending on conditions (temperature, relative humidity, layer thickness, ...)

### Packing & storage

Cans of 5 and 25 l

12 months in original unopened packaging. Store cool, dry, frost-free and protected from sunlight.

### Installation

Thoroughly mix the product before use.  
Apply with a brush, roller or rubber squeegee on a dry, dust- and grease free substrate.  
Allow to dry completely before applying the membrane.  
See label for more information.

#### Cleaning tools:

- wet product: White Spirit

### Certifications



### Special indications

#### Hygiene, Health and Environment

For more information, please refer to the relevant safety data sheet.

#### Quality-, Environment- and Safety Management

**SOPREMA** always recognises as a high level of importance the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.