

## SOPRAVAP GLOBAL PB A 30 TF

### Description

Membrane composed of polymer bitumen and an aluminium reinforcement.  
Used as a vapour control layer on wooden or concrete surfaces for buildings with high moisture production.  
The upper surface is finished with talcum/sand.  
The lower surface is protected by a thermofusible film.

### Composition

	SOPRAVAP GLOBAL PB A 30 TF
Reinforcement	aluminium
Finish upper side	talcum/sand
Finish lower side	thermofusible film
Coating mass	polymer bitumen

### Packing

	SOPRAVAP GLOBAL PB A 30 TF
Dimensions of the roll (m)	10 x 1
Mass of the roll (kg)	40
Number of rolls per pallet	30

### Characteristics

		SOPRAVAP GLOBAL PB A 30 TF
Membrane thickness (mm) (EN 1849-1)	MDV	3,0
Membrane mass (kg) (EN 1849-1) (indicative)	MDV	4,0
Tensile force L (N/5cm) (EN 12311-1)	MDV	NPD
Tensile force T (N/5cm) (EN 12311-1)	MDV	NPD
Elongation at maximum tensile force L (%) (EN 12311-1)	MDV	NPD
Elongation at maximum tensile force T (%) (EN 12311-1)	MDV	NPD
Resistance to tearing (nail shank) L (N) (EN 12310-1)	MDV	NPD
Resistance to tearing (nail shank) T (N) (EN 12310-1)	MDV	NPD
Flexibility at low temperature (°C) (EN 1109)	MLV	-5
Flow resistance at elevated temperature (°C) (EN 1110)	MLV	100
Water vapour diffusion-equivalent (m) (EN 1931)	MDV	4000

MDV = manufacturer's declared value / MLV = manufacturer's limiting value / NPD = no performance determined

## Installation

- Torch-on or hot-air method including the overlaps.

## Certifications

**CE** No.: /  
Standard: **EN 13970**  
Year: **2017**

FM approved



## Special indications

### Hygiene, Health and Environment

The membrane does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.  
For more information, please refer to the relevant safety data sheet.

### Quality-, Environment- and Safety Management

**SOPREMA** always recognises as a high level of importance the quality of the products, the environment and safety.

For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.



Marnix DERKS  
Technical Director  
Grobbendonk, 29/01/2018