

## **DECLARATION OF PERFORMANCE**

**n° WPBEX250**

**Date: August, 18<sup>th</sup> 2015 (rev. c)**

*1 – Unique identification code of the product-type:*

**WPBEX250**

*Commercial name (s):*

**COLPHENE BSW H**

*2 – Intended use(es):*

**Flexible sheets for waterproofing – bitumen damp proof sheets including bitumen basement tanking sheets, type A and T**

*3 – Manufacturer:*

**SOPREMA SAS  
14, rue de Saint-Nazaire – CS 60121  
67100 STRASBOURG  
www.soprema.com**

*4 – Authorised representative:*

**Non applicable**

*5 – System(s) of assessment and verification of constancy of performance:*

**AVCP 2+**

*6a – Harmonised standard: **EN 13969:2004 + A1:2006***

*Notified body(ies):*

**The Kiwa Polymer Institut GmbH (Notified Body n°1119):**

- **performed the inspection of the system of Factory Production Control under system 2+**
- **issued the conformity certificates of Factory Production Control.**

# DECLARATION OF PERFORMANCE

n° WPBEX250

Date: August, 18<sup>th</sup> 2015 (rev. c)

7 – Declared performance(s):

Essential characteristics	Performances	Harmonised Technical Specification
Reaction to fire	<b>E</b>	<b>EN 13969:2004 + A1:2006</b>
Root resistance	<b>NPD</b>	
Peel resistance of joints (N / 50 mm)	<b>≥ 100</b>	
Watertightness	<b>Conform</b>	
Resistance to impact – Method A (mm)	<b>1000</b>	
Shear resistance of joints (N / 50 mm)	<b>≥ 700</b>	
Flexibility at low temperature	<b>≤ -16°C</b>	
Tensile properties: Tensile strength L x T (N / 50 mm) Elongation L x T (%)	<b>800 (±100) x 800 (±100) 45 (±10) x 45 (±10)</b>	
Resistance to static loading – Method B (kg)	<b>10</b>	
Resistance to tearing (nail shank) (N)	<b>250 (±50) x 250 (±50)</b>	
Durability Watertightness after ageing	<b>Conform</b>	
Dangerous substances (Notes 2 and 3)	<b>Complies</b>	

Note 2: This product does not contain asbestos or tar constituents.

Note 3: Since there is no European test method available, no performance declaration for leaching behavior can be made. It must be made according to national rules in force in the place of use.

8 – Appropriate Technical Documentation and/or Specific Technical Documentation:

**Non applicable**

*The performances of the product identified above is in conformity with the set of declared performance (s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.*

Signed for and on behalf of the manufacturer by:

**Strasbourg,  
Export Technical Manager, Mr Pascal MOUGEOT-LUDIN**

