

## COLTACK

**COLTACK** is a high modulus reactive, cold applied adhesive, bitumen-based, polyurethane resin and volatile solvents.

**COLTACK** contains a significant proportion of bio-sourced raw materials from vegetable source.

### User application

**COLTACK** is mainly used to bond alveolar foam thermal insulation\* (expanded polystyrene, polyurethane, polyisocyanurate, ...) onto bituminous vapour barrier with sanded-surface or onto an old bituminous membrane (in case of renovations). Outdoor use only.

All the applications are described in **SOPREMA**'s Technical Guidelines, Technical Approval in force.

\* Please refer to the "Sopralène Stick" Technical Approval.

### Characteristics

	<b>COLTACK</b>
Density at 25°C	1000 ± 50 kg/m <sup>3</sup>
Dry content	88 %
Viscosity at 20°C	6000 mm <sup>2</sup> /s
Flash point (ASTM D 56)	+ 20°C
Dry to touch	< 6 hours
Maximal resistance	After 7 days
Perpendicular tensile adhesion on insulation PSE/PUR/PIR (5 mm / min on 20 x 20 cm)	Break in insulation
* The viscosity is given as indicative.	

### Packaging

- Bucket of 25 kg

**Storage:** **COLTACK** remains stable for 12 months, in unopened original packaging away from humidity and heat at a temperature between + 5°C and 25°C.

Opened bucket can not be stored again.

## Installation

---

**COLTACK** is applied in stripes (watering can) or in pads. The consumption is between 200 and 300 g/m<sup>2</sup>.

Refer to Technical Approvals and **SOPREMA**'s Technical Guidelines in force.

Tools cleaning : **DILUANT V** or **SOPRACLEANER**.

## Special indications

---

### **Hygiene, health and environment:**

Liquid and vapours are flammable.

Follow the recommendations indicated on the packaging. Prior to the flame use, it is mandatory to keep away cans for at least 10 meters, whatever they are opened or not.

For further information, please refer to relevant Safety Data Sheet.

### **Traceability:**

Product traceability is ensured through a manufacturing code present on the packaging.

### **Quality control:**

**SOPREMA** has always attached the highest importance to the quality of its products, to the respect of environment and men.

For this reason, we apply an integrated management of the Quality and Environment certified **ISO 9001** and **ISO 14001**.