

## SOPRASPRAY

### Description

**SOPRASPRAY** is a ready-to-use fast-drying primer composed of bitumen and solvents. It provides excellent adhesion on existing bituminous membranes, metals, insulation boards, wood, concrete, brick and hard PVC. Application on insulation boards based on styrene should be avoided.

### Characteristics

Composition	bitumen and solvents
Consumption	2 - 3,5 m <sup>2</sup> / canister
Application temperature	+10 / +35 °C
Curing time	±30 min. (20 °C)

### Packing & storage

Canister 500 ml

Minimum 12 months in original unopened packaging, stored in a dry and cool place at a temperature between +5 and +25 °C.

### Installation

Apply in a well-ventilated area.  
Shake the canister for 2 minutes before use.  
The surface must be clean, solid and free of dust and grease.  
Spray a uniform coat at a distance of about 30 cm away from the application area.  
After use, place the canister upside-down and purge the valve for a few seconds to avoid clogging.

#### Cleaning tools:

- White Spirit

### Special indications

#### Hygiene, Health and Environment

For more information, please refer to the relevant safety data sheet.

#### Quality-, Environment- and Safety Management

**SOPREMA** always recognises as a high level of importance the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.