

VELAMOUSSE

VELAMOUSSE is a thin underlayer soundproofing material made of polyethylene foam with closed cells.

VELAMOUSSE is laid as underlayer only under wooden laminated floors.

User application

VELAMOUSSE allows the acoustic insulation of floors from impact noise, in compliance with the requirements of NF P 61-203 (common part of DTU 26.2 and 52.1) regarding the installation of insulating underlayer under screed or floating slabs and under tiles.

Composition

	VELAMOUSSE
Nominal thickness	3 mm
Topside	Polyethylene foam with closed cells
Underside	Polyethylene foam with closed cells

Packaging

	VELAMOUSSE	
Dimensions of the roll	20 m x 1,50 m (30 m ²)	80 m x 1,50 m (120 m ²)
Weight of the roll	about 1,5 kg	about 8 kg
Storage	Upright on pallet with plastic wrapping	
<small>Roll lengths are given with a tolerance of < 1 %. Width of roll is given with a tolerance of 1% (UEAtc). Rolls must be stored upright on flat ground. During storage, protect the rolls against moisture. In cold weather, we recommend that the rolls be kept at a minimum temperature of + 2°C (+ 36 °F) for at least 5 hours before installation.</small>		

Special indications

Hygiene, health and environment:

The product does not contain any substance likely to be detrimental to health or to environment and complies with generally admitted Health and Safety Requirements. For further information, please refer to relevant Safety Data Sheet.

Quality control:

SOPREMA has always attached the highest importance to the quality of its products, to the respect of environment and men.

For this reason, we apply an integrated management of the Quality and Environment certified **ISO 9001** and **ISO 14001**.