

# STRATOS R6

## COLD ASPHALT REPAIR

### USE

STRATOS R6 is a cold asphalt mix based on polymer modified bitumen.

STRATOS R6 allows a quick and easy application in both new construction (parking decks, driveways, ...) and renovation (potholes, ...).

After repair, the surface presents the same characteristics than the rest of the asphalted area. Depending the weather conditions, the product will reach the required resistance after 10 to 20 days after application.



### DESCRIPTION

STRATOS R6 is a cold applied mix consisting of polymer modified bitumen embedded gravel.

A 25 kg bucket allows to cover  $\pm 1 \text{ m}^2$  with a thickness of  $\pm 10 \text{ mm}$ .

A disposable liner bag allows bucket reuse and traditional waste treatment.

### ADVANTAGES

- easy and quick to apply
- cold applied
- immediate traffic circulation possible

### APPLICATION

The substrate must be dry, clean and free from dust, grease and of non-adherent substances.

STRATOS R6 is poured in excess on the area to be treated and subsequently compacted and levelled to be plane with the surrounding area. In case of immediate traffic circulation, STRATOS R6 needs to be topped of with sand.

STRATOS R6 can be applied in successive layers up to 5 cm, without exceeding a total thickness of 10 cm.

STRATOS R6 is preferably applied at a temperature above  $+ 10 \text{ }^{\circ}\text{C}$ .

## CHARACTERISTICS

Technical characteristics	Standard	Unit	Value	Tolerance
Density		kg/dm <sup>3</sup>	1,6 to 1,8	
Grain size			0/4	
Type of aggregates			limestone	
<b>Packing</b>			<b>STRATOS R6</b>	
Size		kg	20 x 1 (packed individually)	

## SPECIAL INDICATIONS

### HYGIENE, HEALTH AND ENVIRONMENT

The product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.  
For more information, please refer to the relevant safety data sheet.

### QUALITY-, ENVIRONMENT- AND SAFETY MANAGEMENT

**SOPREMA** always recognises as a high level of importance the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.