

PRODUCT INFORMATION

DESCRIPTION

FLAGOFIL is a cord realized in PVC.

USE

FLAGOFIL PVC is a protection element that is applied on roofing in waterproofing systems made with FLAGON PVC synthetic membranes.

APPLICATION

FLAGOFIL is used welded on one side (external) of the prepunched FLAG bar placed along the entire perimeter of the roof and of the vertical elements present on the roof in order to counteract the horizontal translation actions of the PVC membrane. FLAGOFIL is welded with Leister hot air gun by using a special nozzle directly on Flagon PVC synthetic membrane.

CHARACTERISTIC

- Excellent weldability with Flagon PVC membranes



CHARACTERISTIC

Weigh	(g/cm ³)	1,28	ISO 1183
Hardness	(shore A)	74	ISO 868
Tensile strength	(N/mm ²)	12,0	ISO 527-1,2
Elongation at break	(%)	280	ISO 527-1,2

PACKAGING

Diameter	4 mm
Color	Light blue or White
ml for pack	200 ml

NOTE

Laying by installer approved by Soprema srl.

UNI EN ISO 9001 (Quality Company System) and UNI EN ISO 14001 (environmental system) certified quality system.

The data herewith indicated are not exhaustive and Soprema srl may modify them without previous notice. Soprema srl, has the right to modify the product at any time and without previous notice, in any of its aspect, and to stop its production. In case of dispute the official version of this sheet product information will be provided directly by the technical office Soprema srl stamped and signed by the technical manager. Soprema srl reserves the right, as technology and know-how progress, to modify without warning the composition and conditions of use of its materials, and subsequently their price. As a result, orders shall only be accepted on the basis of the terms and technical specifications applicable at the time of receipt.