



- Breather membrane with proven long term moisture protection for clad walls with up to 30 mm open jointed cladding
- The highly UV-resistant membrane withstands the 5000 h UV test (providing durable and discreet protection for the building)
- Matching system accessories incl. PAVATEX system guarantee

### Packaging

Roll width [m]	Roll length [m]	Roll area [m <sup>2</sup> ]	Roll weight [kg]
1,5	50	75	15

### Characteristics

Material	coated polyester	
Thickness [mm]	0,35	
S <sub>d</sub> value [m]	0,02	
Specific weight [g/m <sup>2</sup> ]	200	
Resistance to water penetration	W1	
Temperature resistance [°C]	-40 to +80	
Minimum installation temperature [°C]	to match the adhesive	
Reaction to fire (EN 13501-1)	E	
Dimensional stability	longitudinal	0,1
	transversal	0,2
Tensile force [N/5cm]	longitudinal	270
	transversal	230
Elongation at maximum tensile strength [%]	longitudinal	35
	transversal	35
Resistance to tearing (nail shank) [N]	longitudinal	110
	transversal	110



### Product description

PAVATEX FBA is a facade membrane that is both vapour-permeable and highly UV-resistant, for open rear-ventilated facades with a maximum joint size of 30 mm. The membrane protects the construction reliably from precipitation and also serves as windproofing while meeting visual requirements for open cladding.

The black coating is resistant to direct and indirect UV radiation and makes the product very durable. As a result the membrane meets the high requirements of SIA 232/2 and also of EN 13859-2 and has withstood the 5000 h UV test.

If mechanically secured, PAVATEX FBA can be left exposed to the weather for 3 months.

Bonding of the longitudinal joints can be done with PAVAFIX or with PAVABOND.

Always consult the local regulations and installation guidelines of the manufacturer.

### Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

For more information, please refer to the relevant safety data sheet.

### Storage

Store cool and dry, lying down or upright, protected from sunlight and humidity.