

## TECHNICAL DATASHEET

# **SOPRA XPS Upstand Board**

## **Description**

**SOPRA XPS Upstand Board** is a rigid thermal insulation board made of extruded polystyrene (XPS) foam on one side a hard cement-based facing.

SOPRA XPS Upstand Board is mainly used as thermal insulation for upstands of flat roofs and underground walls.

## **Packing & Storage**

Thickness (mm) (1)	Boards/pallet	m²/pallet	Thermal resistance (R <sub>D</sub> ) (m <sup>2</sup> .K/W) (2)
26 (20+6)	84	60,5	0,60
36 (30+6)	60	43,2	0,90
46 (40+6)	48	34,6	1,20
56 (50+6)	42	30,2	1,50
66 (60+6)	32	23,0	1,80

<sup>(1)</sup> Thickness insulation + the thickness of the cement-based facing (6 mm).

Store the insulation boards on a flat surface, keep dry, protected from sunlight and temperatures above 75 °C.

### **Characteristics**

Thermal conductivity (W/(m.K)) (EN 12667) (3)	0,033	
Length (mm) (EN 822)		1200 ± 8
Width (mm) (EN 822)		600 ± 8
Density (kg/m³) (3)		30-35
Edge profile		straight
Surface (3)	The state of the s	smooth
Compressive strength at 10% deformation (kPa) (EN 826) (3)	≤ 20 mm > 20 mm	CS(10\Y)250 CS(10\Y)300
Dimensional stability (%) (EN 1604) (3)	> 20 mm	DS(70,90)
Long term water absorption by immersion (%) (EN 12087) (3)	> 20 mm	WL(T)0,7
Reaction to fire (EN 13501-1) (3)		E
Water vapour permeability (µ) (EN 12086)	> 20 mm	150
Tensile strength perpendicular to faces (kPa) (EN 1607) (3)	> 20 mm	TR200
Compressive creep (kPa) (EN 1606) (3)		NPD
NDD		

NPD = no performance determined

#### **Installation**

Always consult the local regulations and contact the manufacturer for technical questions. Immediately after installation the insulation boards must be protected against weather conditions, sunlight and temperatures above 75 °C.

## **Special indications**

#### Hygiene, Health and Environment

The product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

### **Quality-, Environment- and Safety Management**

**SOPREMA** always recognises as a high level of importance the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.

SOPREMA

TDS-NE-INSBE0028.a/EN

**SOPREMA** reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order.

<sup>(2)</sup> Insulation (see declaration of performances INSES0102)

<sup>(3)</sup> Insulation (see declaration of performances INSES0102)