



SOPREMA

Solution for wood decking



durable
 water resistant
 aesthetic
 Pedestrian access

daldécor

SOPREMA
GROUP

water resistant
durable
aesthetic



Daldécor is a wood decking tile for floating paving system for exterior to be used with fixed or adjustable paving support pads and designed for pedestrian access. Made with maritime pine wood, its natural color reveals wood grains.

daldécor

Daldécor is intended to pedestrian traffic on roofs and terraces.

The slabs can be placed on pads for an overloading on private terraces limited to less than 250 kg/m² or directly on any substrate.

Daldécor can also be used to protect sterile zone of **Sopranature**[®] vegetated terraces.



daldécor

- + **Aesthetic:** Natural pine ensures terraces a particularly neat finish; **Daldécor** blends perfectly well with most architectural styles. **Daldécor** is made with a particular chosen wood, with a maximum of 3 singularities structure on the top face and 5 on the cons-side.
- + **Durable:** Pine wood used comes from sustainably managed forests (PEFC certified) and is treated against biological attack (Class 4 certified CTB-P + FCBA). **Daldécor** has an anti-fungal warranty up to 10 years. Slabs are assembled with stainless steel nails providing a protection to avoid corrosion.
- + **Water-Resistant:** **Daldécor** can withstand without deterioration prolonged contact with water.



TECHNICAL DATA AND PACKAGING

- Dimensions : 500 x 500 mm.
- Thickness : 44 mm.
- Configuration : 7 surface slats and 2 support slats.
- Weight 14 kg/m².
- Number of decks / bag: 4 units(1 m²).
- Number of bags / pallet: 28 units.
- Number of m² / pallet: 28 m².



for wood decking

ACCESSORIES

- Finishing slats (pack of 10).
- Stainless steel nails (box of 1 kg).
- Quarter-round finishing moulding (pack of 10 X 2 m).
- Linking plates (pack of 100).
- **SOPREMA** polypropylene fixed pedestals, available in 2 heights:
 - 8 mm (100 units box).
 - 35 mm (60 units box).
- **SOPREMA** polypropylene screw-jack pedestals. Available in 4 adjustable heights:
 - 40 to 67 mm (120 units box).
 - 60 to 90 mm (60 units box).
 - 90 to 150 mm (60 units box).
 - 150 to 260 mm (48 units box).

The screw-jack pedestal consists of 2 parts: a base and a screw device. The tiles are levelled continuously and effortlessly as they are laid by activating the adjustable screw using the special spanner supplied in each carton. 5 pads per m² are required to lay the **Daldécor** tiles.

The **SOPREMA** pedestals have their own Technical Data Sheet.

Shock-absorbing shims may be placed on the tops of the pedestals for added acoustic comfort (100 units box).

INSTALLATION

- **Daldécor** can be laid simply on pedestals or directly on the underlying surface. Metal assembly plates (supplied with the tiles) are used to fasten the tiles together.
- For a complete description of how to lay a «tiles on pedestals» waterproofing system, see the «waterproofing solutions» folder.
- **Daldécor** is covered by the Technical Approval: **Elastophene® Flam** / **Sopralene Flam®** as well as the Technical Approval: **Sopralène Flam® Unilay** under heavy protection.





SOPREMA GROUP at your service

Looking for a sales contact in order to discuss a future project or a project that is under way? Any questions about the implementation of our product range?

Contact Soprema Export Department

Tel.: +33 (0)3 88 79 84 84 - Fax: +33 (0)3 88 79 84 85

Email: export@soprema.com

Find all the information on www.soprema.com



A project under way
We have solutions!
www.soprema.com
Tel. +33 3 88 79 84 84



SOPREMA

GROUP

e-mail: contact@soprema.com - www.soprema.com