

## **DECLARATION OF PERFORMANCE**

N° WPBBE0434

Unique identification code of the product type: DuO HT 4 AGR/F C180 FC

Intended use(s): Reinforced bituminous sheet for roof waterproofing

Manufacturer: Soprema NV

Bouwelven 5 - 2280 Grobbendonk

Belgium

System(s) of AVCP: system 2+

Harmonised standard: **EN 13707:2004 + A2:2009** 

Notified body/ies: **0749** 

Declared performances

Declared performances  Essential characteristics			Performances		Test standard	Harmonised standard
External fire performance (note 1)		Froof(t1, t2, t3, t4)		EN 13501-5		
Reaction to fire			E		EN 13501-1	
Watertightness	The second second	(kPa/24 h)	≥ 10		EN 1928-A	
Tensile strength:  Elongation at maximum	longitudinal transversal	(N/50 mm) (N/50 mm)	880 880	± 20 % ± 20 %	EN 12311-1	
Liongation at maximum	longitudinal transversal	(%) (%)	50 50	± 15 ± 15	LN 12311-1	
Resistance to root penetration			NPD		EN 13948	
Resistance to static loading		(kg)	≥ 25		EN 12730-A	EN 13707:2004 + A2:2009
Resistance to impact		(mm)	≥ 1000 ≥ 1000		EN 12691-A EN 12691-B	
Resistance to tearing (nail shank)		(N)	335	± 25 %	EN 12310-1	
Joint properties:	peel resistance shear resistance	(N/50 mm) (N/50 mm)	235 670	± 25 % ± 25 %	EN 12316-1 EN 12317-1	
Behaviour after artificial aging					EN 1296 +	
durability UV, heat and water			NPD		EN 1297	
flow resistance at elevated temperature (°C) flexibility at low temperature (°C)		100 -5/-5	-0/+20 -15/+0	EN 1110 EN 1109		
Flexibility at low temperature (°C)			≤ -15/-20		EN 1109	
Dangerous substances (note 2)			note 3		-	

NPD = no performance determined

1) since external fire performance depends on the other components of the roof build-up, no performance can be given

this product does not contain asbestos or tar constituents

3) in the absence of European harmonized test methods, verification and declaration on release and content has to be done taking into account national provisions in the place of use

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Marnix Derks, Technical Director Grobbendonk, 10/03/2020

