



- Light, stable and insulating
- Quick installation
- Vapour control and air-tight, finished surface for finishing work

### Packaging

Thickness [mm]	Boards/pallet	Dimensions <sub>net</sub> [mm]	m <sup>2</sup> <sub>net</sub> /pallet [m <sup>2</sup> ]	Dimensions [mm]	m <sup>2</sup> /pallet [m <sup>2</sup> ]	Mass/pallet [kg]	Thermal resistance (R <sub>d</sub> ) [m <sup>2</sup> .K/W]
30	74	1230 x 520	47,3	1250 x 540	50,0	360	0,65
30	74	2480 x 520	95,4	2500 x 540	99,9	709	0,65
60	72	1230 x 520	48,6	1250 x 540	48,6	691	1,35
60	36	2480 x 520	46,4	2500 x 540	48,6	691	1,35

Production: France

### Characteristics

Density [kg/m <sup>3</sup> ]	230
Thermal conductivity (λ <sub>d</sub> ) (EN 13171) [W/(m.K)]	0,044
Specific heat capacity (c) [J/(kg.K)]	2100
S <sub>d</sub> value [m]	2
Reaction to fire (EN 13501-1)	E
Compressive strength at 10 % deformation [kPa]	250
Tensile strength perpendicular to faces [kPa]	30
Waste code according to The European Waste Catalogue (EWC)	030105; 170201; 170604
Edge profile	tongue - groove

### Product description

PAVAROOM is a natural and ecological, thermal and contact sound-insulating board based on wood fiber finished with a hard cellulose facing.

The board can be used universally in the interior finish of walls, attics and ceilings.

The coating fulfills the function of vapour control, using an extra vapour control membrane is not required.

Thanks to the coating and the tongue and groove finishing, one can save up to 3 steps in comparison with plasterboard, which enables quick installation.

The combination with PAVAFIX WIN sealing tape guarantees a high airtightness to the building.

Always consult the local regulations and installation guidelines of the manufacturer.

### Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

For more information, please refer to the relevant safety data sheet.

### Storage

Store the insulation boards on a flat surface, keep dry and protected from sunlight.

Stack no more than 2 pallets on top of each other.

