



- Solvent-free and without odour
- Fast, controlled hardening, adheres to moist surfaces
- Taping of overlaps and connections at PAVATEX membranes and as adhesive medium for PAVATAPE

Packaging

| | Contents per container [ml/g] | Box contents [units] | Accessories included |
|-------------|----------------------------------|-------------------------|--------------------------|
| Cartridge | 310/470 | 12 | 12 snap-off nozzles |
| Tubular bag | 600/900 | 10 | 10 large conical nozzles |

Characteristics

| | |
|---|---|
| Material | 1-component polyurethane adhesive, solvent-free |
| Minimum installation temperature for base and air [°C] | -5 |
| Installation temperature adhesive [°C] | +5 to +40 |
| Temperature resistance [°C] | -40 to +110 |
| Open time (skin formation time) at 20 °C and 65 % r.h. [min.] | 7 |
| Tight after [h] | 2 |

Product description

For waterproof and weatherproof gluing of PAVATEX insulation and sarking systems, and for waterproof and airtight gluing of overlaps and connections at PAVATEX membranes. As adhesive medium for PAVATAPE on moist and open-pored surfaces. Also adheres to wood, boards of wooden material, non-combustible construction boards, concrete, brickwork, render, corrosion-protected metals and damp substrates.

Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements. For more information, please refer to the relevant safety data sheet.

Storage

Shelf life: 18 months unopened
Store cool and dry, protected from sunlight.