

SOPRACOL LIQUID

Description

Cold applied ready-to-use, viscous adhesive based on a bituminous binder and solvents.

It is used for the full bonding of bituminous membranes with gluable finish such as sand.

It is suitable on substrates such as bituminous membranes with sand or mineral-finish, concrete, wood, metal and insulation boards with suitable finish such as bitumen coating.

It is also suitable for old / weathered bituminous waterproofing membranes with a slate or granulate finish.

Characteristics

Composition	bituminous binder and solvents
Consumption	± 1 kg/m ²
Application temperature	+5 / +35 °C

Packing & storage

Can of 5 kg and 25 kg

Minimum 12 months in original unopened packaging, stored in a dry and cool place, protected from sunlight at a temperature between +5 °C and +20 °C.

Installation

Apply with a rubber or toothed squeegee on a dry, dust- and grease free substrate.

Suitable for roofs with a slope of ≤ 10 %.

Cleaning tools:

- wet product: SOPRACLEANER or White Spirit

Special indications

Hygiene, Health and Environment

For more information, please refer to the relevant safety data sheet.

Quality-, Environment- and Safety Management

SOPREMA always recognises as a high level of importance the quality of the products, the environment and safety.

For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with

EN ISO 9001 and **EN ISO 14001**.