

BANDE LM SOPRAJOINT

BANDE LM SOPRAJOINT is a mineral wool roll laid under SOPRAJOINT elastomeric membrane used for expansion joints.

User application

All the applications are described in Technical Approvals or **SOPREMA**'s Technical Guidelines in force.

Composition

| | BANDE LM SOPRAJOINT |
|-------------------|---|
| Nominal thickness | 35 mm (about 10 mm when SOPRAJOINT is installed) |
| Topside | Mineral wool |
| Underside | Mineral wool |

Packaging

| | BANDE LM SOPRAJOINT |
|--|--|
| Dimensions of the roll | 10 m x 0,15 m |
| Weight of the roll | about 1 kg |
| Storage | Upright on pallet with plastic wrapping, protected from moisture |
| <small>Roll lengths are given with a tolerance of < 1 %. Width of roll is given with a tolerance of 1% (UEAtc). Rolls must be stored upright on flat ground. During storage, protect the rolls against moisture. In cold weather, we recommend that the rolls be kept at a minimum temperature of + 2°C (+ 36 °F) for at least 5 hours before installation.</small> | |

Special indications

Hygiene, health and environment:

The product does not contain any substance likely to be detrimental to health or to environment and complies with generally admitted Health and Safety Requirements.

Quality control:

SOPREMA has always attached the highest importance to the quality of its products, to the respect of environment and men.

For this reason, we apply an integrated management of the Quality and Environment certified **ISO 9001** and **ISO 14001**.