

Product description:

ALSAN 601 Cleaner is a solvent applied for viscosity adjustments and tool cleaning in conjunction with the products of the Alsan 601 range.

**Application areas**

ALSAN 601 Cleaner is fully compatible with the ALSAN 601 product range. It is suitable for in-situ viscosity adjustments and tool cleaning.

Implementation**Mixing:**

See corresponding technical data sheet.

Application:

Use a suitable container when transferred for cleaning. See corresponding technical data sheet when used for viscosity adjustments (diluting).

Consumption

Depending the application

Technical characteristics

Density (20 °C): 0,86 g/cm³

Viscosity (20 °C): >1 mPa.s

Packing

4 / 20 kg metal container

Storage, transport & shelf life

In its original unopened package stored in a cool, dry and frost-free place at a temperature below +35 °C away from ignition sources, the unmixed product has a minimum shelf life of 12 months.

Safety information and risks

Refer to the relevant safety data sheet for more information. Pay attention to the personal protective equipment.

Elimination

Cured material may be disposed of as construction waste. Containers and uncured material must be disposed of as a hazardous waste.

Manufactures/company

Soprema nv
Bouwelven 5
2280 Grobbendonk
Belgium

General information

The information in this document is applicable to the corresponding product, provided by Soprema. Please note that this may vary from country to country. The above information, in particular the product application information, is based under normal circumstances and is provided to the best of our knowledge. The wide variety of requirements and conditions on site requires that the product must be tested by the user under the specific conditions to ensure that it is suitable for the intended use. We reserve the right to make changes that reflect the technological progress and improvements to our products.