

1 – Unique identification code of the product-type:

INSFR005

Commercial name (s):

EFIGREEN ALU +

EFIGREEN ALU + XL

2 – Intended use(es):

Thermal insulation products for buildings

3 – Manufacturer:

**SOPREMA SAS
14, rue de Saint-Nazaire – CS 60121
67100 STRASBOURG cedex
www.soprema.com**

4 – Authorised representative:

Non applicable

5 – System(s) of assessment and verification of constancy of performance:

AVCP 3

6a – Harmonised standard:

EN 13165:2012 + A2:2016

Notified body(ies):

LNE (Laboratoire National de métrologie et d'Essais), notified body n°0071:
- made the determination of the product-type on the basis of type testing,
- issued the corresponding tests reports,
according to system 3.

7 – Declared performance(s):

Essential characteristics	Performances		Harmonised Technical Specification
Thermal conductivity - λ_D (W/(m.K))	0,023	0,022	EN 13165:2012 + A2:2016
Thickness - d (mm)	30-35	40-160	
Thermal resistance - R (m ² .K/W)	1,30-1,50	1,80-7,25	
Classes for thickness tolerances	T2		
Reaction to fire	NPD		
Durability of reaction to fire depending on heat exposure, bad weather, ageing/deterioration	(a)		
Durability of thermal resistance depending on heat exposure, bad weather, ageing/deterioration	NPD		
Characteristics for durability			
Dimensional stability			
Deformation under specified compressive load and temperature conditions			
Thermal resistance and thermal conductivity values after ageing	(b)		
Compressive strength	CS(10\Y)200		
Tensile strength	TR150		
Durability of compressive strength depending on ageing/deterioration	NPD		
Compressive creep			
Water permeability	WS(P)0,2		
Water absorption in short time			
Water absorption in long time			
Flatness after partial immersion	NPD		
Water vapour transmission	NPD		
Acoustic absorption index	NPD		
Release of dangerous substances inside buildings	(c)		
Continuous glowing combustion	(c)		

(a): PU fire performance does not degrade with time.

(b): Any variation for thermal conductivity and thermal resistance is processed and considered in the reported values (Annex C for the thermal conductivity and dimensional stability for the thickness).

(c): European test methods are on-going.

8 – Appropriate Technical Documentation and/or Specific Technical Documentation:

Non applicable

The performance of the product identified above is in conformity with the set of declared performance (s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Strasbourg, 06th September 2018 (ver. c)
Export Technical Manager, Mr Pascal MOUGEOT-LUDIN

