

SOPRASPRAY

Description

SOPRASPRAY is a ready-to-use fast-drying primer composed of bitumen and solvents. It provides excellent adhesion on existing bituminous membranes, metals, insulation boards, wood, concrete, brick and hard PVC. Application on insulation boards based on styrene should be avoided.

Characteristics

Composition	bitumen and solvents
Consumption	2 - 3,5 m ² / canister
Curing time *	±30 min. (20 °C)
Application temperature	+10 / +35 °C

* Depending on conditions (temperature, relative humidity, layer thickness, ...)

Packing & storage

Canister 500 ml

Minimum 12 months in original unopened packaging, stored in a dry and cool place at a temperature between +5 and +25 °C.

Installation

Substrate preparation:

The substrate must be prepared to ensure it is sound, dry and free from adhesion-reducing residues. Polymer modified mortars and fast curing cement require a compatibility check on site.

Application:

Apply in a well-ventilated area.

Shake the canister for 2 minutes before use.

The surface must be clean, solid and free of dust and grease.

Spray a uniform coat at a distance of about 30 cm away from the application area.

After use, place the canister upside-down and purge the valve for a few seconds to avoid clogging.

Cleaning tools:

- White Spirit

Special indications

Hygiene, Health and Environment

For more information, please refer to the relevant safety data sheet.

Quality-, Environment- and Safety Management

SOPREMA always recognises as a high level of importance the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.