

Product description:

ALSAN FLEECE 165 P is a non-woven perforated polyester fleece specially designed for use with the ALSAN FLASHING QUADRO waterproofing resin.



Application areas

ALSAN FLEECE 165 P is used as reinforcement and ensures a minimum layer thickness of the ALSAN FLASHING QUADRO waterproofing resin must be applied. The combination provides a high-quality flexible and crack-bridging waterproofing system.

Properties

- polyester fleece
- improves the bridging crack
- makes it possible to control the layer thickness
- very good resistance to decomposition
- mechanically and thermally bonded

Conditions for application

The conditions of use depend on the resins used.

Implementation

See technical data sheet of ALSAN FLASHING QUADRO

Consumption

Depending on the desired application.

Technical characteristics

Density: $\pm 165 \text{ g/m}^2$

Packing

Width (cm)	Roll length (m)
20	50
25	50
30	50
35	50
105	50

Storage, transport & shelf life

Store in a dry place protected from moisture and pollution.

Elimination

Dispose of as construction waste, even if cured resin residues adhere to it.

Manufacturer/company

SOPREMA SAS
14, rue de Saint-Nazaire
67025 Strasbourg
France

General information

The information in this document is applicable to the corresponding product, provided by Soprema.

Please note that this may vary from country to country.

The above information, in particular the product application information, is based under normal circumstances and is provided to the best of our knowledge.

The wide variety of requirements and conditions on site requires that the product must be tested by the user under the specific conditions to ensure that it is suitable for the intended use.

We reserve the right to make changes that reflect the technological progress and improvements to our products.