DECLARATION OF PERFORMANCE

n° WPLFR005

Date : June, 30th 2013

1 – Unique identification code of the product-type:

WPLFR005

2 - Identification of construction product, in accordance with article 11 § 4 of regulation (EU) N° 305/2011 :

ALSAN 500

3 – Intended use (or uses) of the construction product :

Polyurethane resin for liquid waterproofing applications

4 - Name, registered trade name or registered trademark and contact address of the manufacturer, in accordance with article 11 § 5 of Regulation (EU) N° 305/2011 :

SOPREMA SAS
14, rue de Saint-Nazaire – CS 60121
67100 STRASBOURG
www.soprema.com

5 – Name and contact address of the authorised representative whose mandate covers the tasks specified in article 12 § 2 of Regulation (EU) N° 305/2011 :

Non applicable

6 – System (or systems) of assessment and verification of constancy of performance of the construction product as set out in Annex V of Regulation (EU) N° 305/2011 :

AVCP 3

7 – Case of the declaration of performance concerning a construction product covered by a harmonised standard :

Non applicable

8 - Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :

CSTB (Notified Body n° 0679):

- **made the determination of the product-type on the basis of type testing, according to system 3**
- **delivered the ETA-07/0111 according to ETAG 005 : 2004.**

DECLARATION OF PERFORMANCE

n° WPLFR005

Date : June, 30th 2013

9 – Declared performances :

Essential characteristics	Performances	Harmonised Technical Specification
Minimum layer thickness	**1.1 mm**	**ETAG 005 : 2004**
Factor of water vapour diffusion (μ)	**≥ 650**	
Resistance to wind loads	**≥ 50 kPa**	
External fire performance (Note 1)	**F_{ROOF}**	
Reaction to fire	**F**	
Statement on dangerous substances	**No dangerous substances**	
Resistance to slipperiness	**NPD**	
Categories of intended use according ETAG 005		
Expected working life	**W2**	
Climatic zone	**S**	
User loads	**P3**	
Roof slopes	**S1 to S4**	
Minimum surface temperature	**TL4**	
Maximum surface temperature	**TH3**	

Note 1 : Since external fire performance depends on the other components of the roof build-up, no performance can be given.

10 – The performances of the product identified in points 1 and 2 are in conformity with the declared performances in point 9.

This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :

Strasbourg,
Export Technical Manager, Mr Pascal MOUGEOT-LUDIN

SOPREMA SAS with a Capital of 50 000 000 € - Headquarter: 14 rue de Saint-Nazaire – 67100 STRASBOURG – France
Postal adress: CS 60121 - 67025 STRASBOURG CEDEX. RCS STRASBOURG: 314 527 557.
Tel: 03 88 79 84 84 – Fax. : 03 88 79 84 85
www.soprema.com - E-mail : export@soprema.com