

TECHNICAL DATASHEET



SOPRA XPS 700

Description

SOPRA XPS 700 is a rigid thermal insulation board made of extruded polystyrene (XPS) foam produced according to climate-friendly CO_2 technology.

SOPRA XPS 700 is mainly used as thermal insulation including floors and car parks where a very high compressive strength is required.

Packing & Storage

Thickness (mm)	Boards/pack	m²/pack	Boards/pallet ⁽¹⁾	m²/pallet ⁽¹⁾	Thermal resistance (R _D) (m ² .K/W)
50	8	6,00	96	72,0	1,50
60	7	5,25	84	63,0	1,80
80	5	3,75	60	45,0	2,25
100	4	3,00	48	36,0	2,85
120	3	2,25	42	31,5	3,40
140	3	2,25	36	27,0	4,00
160	2	1,50	32	24,0	4,55
180	2	1,50	28	21,0	5,10
200	2	1,50	24	18,0	5,70
220	2	1,50	24	18,0	6,10
240	1	0,75	20	15,0	6,65
260	1	0,75	18	13,5	7,20
280	1	0,75	16	13,5	7,75
300	1	0,75	16	12,0	8,30

⁽¹⁾ In addition to the default pallet, there is also a "jumbo" pack, composed of 2x2 pallets.

Store the insulation boards on a flat surface, keep dry, protected from sunlight and temperatures above 75 °C.

Characteristics

Thermal conductivity (W/(m.K)) (EN 12667)	30 - 60 mm 70 - 200 mm 210 – 300 mm	0,033 0,035 0,036	
Length (mm) (EN 822)		1250 ± 8	
Width (mm) (EN 822)		600 ± 8	
Density (kg/m³)		40-45	
Edge profile		rebate	
Surface		smooth	
Compressive strength at 10% deformation (kPa) ((EN 826)	CS(10\Y)700	
Dimensional stability (%) (EN 1604)		DS(70,90)5	
Long term water absorption by immersion (%) (E	N 12087)	WL(T)0,7	
Reaction to fire (EN 13501-1)	Е		
Water vapour permeability (µ) (EN 12086)		150	
Tensile strength perpendicular to faces (kPa) (EN	1607)	TR200	
Compressive creep (kPa) (EN 1606)		CC(2/1,5/50)250	
D = no porformanco dotorminod			

 \overline{NPD} = no performance determined

Installation

Use a suitable adhesive for adhesion to underground walls.

Always consult the local regulations and contact the manufacturer for technical questions.

Immediately after installation the insulation boards must be protected against weather conditions, sunlight and temperatures above $75\,^{\circ}\text{C}$.

SOPREMA

TDS-NE-INSES0104.f/EN



TECHNICAL DATASHEET



Certifications

- KEYMARK (EU) ATG 3135 (B)

Special indications

Hygiene, Health and Environment

The product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

Quality-, Environment- and Safety Management

SOPREMA always recognises as a high level of importance the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with EN ISO 9001 and EN ISO 14001.

TDS-NE-INSES0104.f/EN

