

# ELASTOCOL 600

## Description

Cold applied primer based on elastomer bitumen and solvents.  
Impregnation to ensure good adhesion to the substrate (concrete, metal and wood) before applying self adhesive bitumen based waterproofing membranes.

## Characteristics

Composition	elastomer bitumen and solvents
Curing time *	1 - 12 h
Consumption (l/m <sup>2</sup> )	0,25 - 0,80
Application temperature (°C)	min. +5

\* Depending on conditions (temperature, relative humidity, layer thickness, ...)

## Packing & storage

Cans of 1, 5 and 30 l

12 months in original unopened packaging. Store cool, dry, frost-free and protected from sunlight.

## Installation

Thoroughly mix the product before use.  
Apply with a brush, roller or rubber squeegee on a dry, dust- and grease free substrate.  
Allow to dry completely before applying the membrane.  
See label for more information.

### Cleaning tools:

- wet product: White Spirit

## Certifications



## Special indications

### Hygiene, Health and Environment

For more information, please refer to the relevant safety data sheet.

### Quality-, Environment- and Safety Management

**SOPREMA** always recognises as a high level of importance the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.