

- 1) Unique identification code of the product-type: **PAVATEX ADB (1.5 m) / PAVATEX ADB (3.0 m)**  
 2) Intended use/es: **Underlay for roof covering of discontinuous roofs of buildings  
Underlay for walls**  
 3) Manufacturer: **SOPREMA GmbH - Mallaustraße 59, 68219 Mannheim, Deutschland**  
 4) Authorised representative: ---  
 5) System/s of AVCP: **AVCP 3**  
 6a) Harmonised standard: **EN 13859-1      EN 13859-2**  
 Notified body/ies: ---  
 7) Declared performance/s:

Essential characteristics of the harmonised standards EN 13859-1:2014 and EN 13859-2 : 2014		Test Standard	Performance	Harmonised standard
Reaction to fire		EN ISO 11925-2	E	EN 13859-1:2014    EN 13859-2:2014
Watertightness		EN 1928	W1	
Water vapour resistance		EN ISO 12572	0.03±0.02 m	
Tensile properties	Maximum force MD / CD	EN 12311-1	315±50 / 250±50 N/5cm	
	Elongation MD / CD		55±15 / 45±15 %	
Resistance to tearing MD / CD		EN 12310-1	220±50 / 230±50 N	
Flexibility at low temperature (pliability)		EN 1109	≤ -20°C	
Durability: Artificial ageing behaviour, concerning	Resistance to water penetration	EN 1928	W1	
	Maximum force MD / CD	EN 12311-1	300±50 / 200±50 N/5cm	
	Elongation MD / CD		50±8 / 40±8 %	
Dangerous substances			NPD	

NPD = No performance determined

8) Appropriate Technical Documentation and/or Specific Technical Documentation:

*The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.*

Signed for and on behalf of the manufacturer by: **Christian JOCHUM, Technical Director**

at : **Mannheim**

on: **04.06.2020**

