

EXODALLE

EXODALLE is a wood decking tile for floating paving system for exterior and used with fixed or adjustable paving support pads and designed for pedestrian access (for collective and public use).

User application

EXODALLE is used on balconies, patios, roof decks for pedestrian access.

All the applications are described in the french DTU, **SOPREMA's** Technical Guidelines, Technical Approval in force.

Composition

EXODALLE is made of MASSARANDUBA wood with a red and brown aspect.

Characteristics

	EXODALLE
Dimensions	50 cm x 50 cm
Thickness	38 mm (2 x 19 mm)
Configuration	7 surface slats and 2 support slats
Slat surface	68 mm
Number of screws	14 (stainless steel)
Density	1,10
Puncture resistance (NF B 51-013)	14 class (Monnin test)
Tensile modulus with a flexibility of 12 %	24410 MPa
Maximum load (NF EN 1339) (pedestrian access only)	T11 (collective and public use)

Packaging

	EXODALLE
Weight	28 kg/m ²
Numbers of slabs / bag	4 U (1 m ²)
Number of bags / pallet	36 U
Number of m ² / pallet	36 m ²

Installation

EXODALLE ensures a fast, simple and durable system of suspended deck finishing as well as paving slabs without battens.

Keep in mind that you might need extra tiles if you have to cut any of them to fit odd shaped areas or curves.

After adjustment of support pads, start by laying them at one corner of the area to be covered.

EXODALLE can be taken up at any time to inspect deck, clean or carry out repairs.

Special indications

Hygiene, health and environment:

The product does not contain any substance likely to be detrimental to health or to environment and complies with generally admitted Health and Safety Requirements. For further information, please refer to relevant Safety Data Sheet.

Quality control:

SOPREMA has always attached the highest importance to the quality of its products, to the respect of environment and men.

For this reason, we apply an integrated management of the Quality and Environment certified **ISO 9001** and **ISO 14001**.