

## PRODUCT INFORMATION

### DESCRIPTION

The PVC CONICAL PIPE COLLAR is a prefabricated element obtained by molding and is made of PVC FLAGON.

### USE

The PVC CONICAL PIPE COLLAR is used on roofing in waterproofing system realized with FLAGON PVC synthetic membranes to give continuity to the waterproofing around elements that come out from the roof.

### APPLICATION


The PVC CONICAL PIPE COLLAR are welded with Leister hot air gun all along the flange perimeter on the Flagon PVC membranes. Around the elements that come out from the roof it is necessary to place a permanent elastic silicone between the conical pipe collar and the element that come out from the roof and, subsequently, tighten the upper end with a stainless steel clamp.

### CHARACTERISTIC

- Resistant to weathering and UV
- Excellent weldability with Flagon PVC membranes

## CHARACTERISTIC

Width	d1	210 mm
Height	h	120 mm
Thickness	-	2,0 mm
Cone internal diameter (top)		10 mm
Cone internal diameter (bottom)		50 mm



## STORAGE AND PACKAGING

Number of pieces for each pack	10 pz
Weight	0,124 kg/pz
Colour	grey
Application temperature	> 5°C
Storage conditions	Store at > +5°C



### NOTE

Laying by installer approved by Soprema srl.

UNI EN ISO 9001 (Quality Company System) and UNI EN ISO 14001 (environmental system) certified quality system.

The data herewith indicated are not exhaustive and Soprema srl may modify them without previous notice. Soprema srl, has the right to modify the product at any time and without previous notice, in any of its aspect, and to stop its production. In case of dispute the official version of this sheet product information will be provided directly by the technical office Soprema srl stamped and signed by the technical manager. Soprema srl reserves the right, as technology and know-how progress, to modify without warning the composition and conditions of use of its materials, and subsequently their price. As a result, orders shall only be accepted on the basis of the terms and technical specifications applicable at the time of receipt.