

XPS MULTI20

Description

XPS MULTI20 is a rigid thermal insulation board made of extruded polystyrene (XPS) foam produced according to climate-friendly CO2 technology.

XPS MULTI20 is mainly used as thermal insulation including floors and interior walls.

Packing & Storage

Thickness (mm)	Boards/pack	m ² /pack	Boards/pallet ⁽¹⁾	m ² /pallet ⁽¹⁾	Thermal resistance (R _D) (m ² .K/W)
20	21	15,75	252	189	0,60

(1) In addition to the default pallet, there is also a "jumbo" pack, composed of 2x2 pallets.

Store the insulation boards on a flat surface, keep dry and protected from sunlight.

Characteristics

Thermal conductivity (W/(m.K))	0,034
Length (mm)	1250 ± 8
Width (mm)	600 ± 8
Density (kg/m ³)	30 +/- 15 %
Edge profile	smooth edge
Surface	rough
Compressive strength at 10% deformation (kPa) (EN 826)	≥ 250
Long term water absorption by immersion (EN 12087)	WL(T)0,7

Installation

Always consult the local regulations and contact the manufacturer for technical questions.

After installation the insulation boards must be protected against weather conditions and sunlight.

Special indications

Hygiene, Health and Environment

The product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

For more information, please refer to the relevant safety data sheet.

Quality-, Environment- and Safety Management

SOPREMA always recognises as a high level of importance the quality of the products, the environment and safety.

For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with

EN ISO 9001 and **EN ISO 14001**.