

DECLARATION OF PERFORMANCE

n° PROFR002

Date : Mai, 15th 2014

1 – Unique identification code of the product-type:

PROFR002

2 – Identification of construction product, in accordance with article 11 § 4 of regulation (EU) N° 305/2011 :

STRATEC III

3 – Intended use (or uses) of the construction product :

**Underlays for discontinuous roofing
Underlays for wall**

4 – Name, registered trade name or registered trademark and contact address of the manufacturer, in accordance with article 11 § 5 of Regulation (EU) N° 305/2011 :

**SOPREMA SAS
14, rue de Saint-Nazaire – CS 60121
67100 STRASBOURG
www.soprema.com**

5 – Name and contact address of the authorised representative whose mandate covers the tasks specified in article 12 § 2 of Regulation (EU) N° 305/2011 :

Non applicable

6 – System (or systems) of assessment and verification of constancy of performance of the construction product as set out in Annex V of Regulation (EU) N° 305/2011 :

AVCP 3

7 – Case of the declaration of performance concerning a construction product covered by a harmonised standard :

The TSUS (Notified Body n°1301):

- **made the determination of the product-type on the basis of type testing, according to system 3**
- **issued the corresponding tests reports.**

8 – Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued :

Non applicable

**SOPREMA**

Roofing material solutions

DECLARATION OF PERFORMANCE

n° PROFR002**Date : Mai, 15th 2014***9 – Declared performances :*

Essential characteristics	Performances	Harmonised Technical Specification
Reaction to fire	F	EN 13859-1 : 2010 EN 13859-2 : 2010
Resistance to water penetration	W1	
Tensile properties :		
Tensile strength - Longitudinal - Transversal	375 ± 50 N/50 mm 305 [-5 ; +50] N/50 mm	
Elongation - Longitudinal - Transversal	50 [-20 ; +50] % 60 [-10 ; +50] %	
Resistance to tearing (Nail shank) - Longitudinal - Transversal	300 [-75 ; +30] N 370 [-100 ; +30] N	
Flexibility at low temperature (Pliability)	-40°C	
Artificial ageing behavior :		
Resistance to water penetration Tensile strength - Longitudinal - Transversal	W1 350 ± 50 N/50 mm 280 ± 50 N/50 mm	
Elongation - Longitudinal - Transversal	47 [-14 ; +50] % 53 [-14 ; +50] %	
Water vapour transmission properties (Sd)	0,05 [-0,03 ; +0,04] m	EN 13859-2 : 2010

10 – The performances of the product identified in points 1 and 2 are in conformity with the declared performances in point 9.

This declaration of performances is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by :

**Strasbourg,
Export Technical Manager, Mr Pascal MOUGEOT-LUDIN**