



- Compression-resistant board with high load capacity
- Outstanding contact sound insulation
- Versatile application under screeds or parquet



Packaging

Thickness [mm]	Boards/pallet	Dimensions [mm]	m ² /pallet [m ²]	Mass/pallet [kg]	Thermal resistance (R _d) [m ² .K/W]
20	224	1100 x 600	147,8	685	0,40
40	112	1100 x 600	73,9	685	0,85
60	72	1100 x 600	47,5	662	1,30

Production: Switzerland

Characteristics

Density [kg/m ³]	220
Thermal conductivity (λ _d) (EN 13171) [W/(m.K)]	0,046
Specific heat capacity (c) [J/(kg.K)]	2100
Water vapour diffusion resistance coefficient (μ) [-]	5
Reaction to fire (EN 13501-1)	E
Compressive strength at 10 % deformation [kPa]	150
Tensile strength perpendicular to faces [kPa]	10
Waste code according to The European Waste Catalogue (EWC)	030105; 170201; 170604
Edge profile	straight

Product description

PAVABOARD is a natural and ecological sound insulation board based on wood fiber.

The high compression resistance makes the board suitable for use in floor applications such as screeds or parquet.

Always consult the local regulations and installation guidelines of the manufacturer.

Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

For more information, please refer to the relevant safety data sheet.

Storage

Store the insulation boards on a flat surface, keep dry and protected from sunlight.

Stack no more than 4 pallets on top of each other.

