



- Interior finishing board
- Ideal for the coverage of loose fill on floors
- Underlay board for parquet / laminate



Packaging

Thickness [mm]	Boards/pallet	Dimensions [mm]	m ² /pallet [m ²]	Mass/pallet [kg]	Thermal resistance (R _d) [m ² .K/W]
8	140	2500 x 1200	420,0	774	0,15
10	112	2500 x 1200	336,0	774	0,20
12	94	2500 x 1200	282,0	779	0,25
16	70	2500 x 1200	210,0	774	0,30
19	60	2500 x 1200	180,0	788	0,40
19	60	1500 x 1200	108,0	480	0,40

Production: Switzerland

Characteristics

Density [kg/m ³]	225
Thermal conductivity (λ _d) (EN 13171) [W/(m.K)]	0,046
Specific heat capacity (c) [J/(kg.K)]	2100
Water vapour diffusion resistance coefficient (μ) [-]	5
Reaction to fire (EN 13501-1)	E
Compressive strength at 10 % deformation [kPa]	100
Tensile strength perpendicular to faces [kPa]	15
Waste code according to The European Waste Catalogue (EWC)	030105; 170201; 170604
Edge profile	straight

Product description

SWISSISOLANT is a natural and ecological, thermal and contact sound insulating board based on wood fiber.

Always consult the local regulations and placement guidelines of the manufacturer.

Health, Environment and Safety

This product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

For more information, please refer to the relevant safety data sheet.

Storage

Store the insulation boards on a flat surface, keep dry and protected from sunlight.

