

SOPRADERE QUICK

Description

Cold applied fast drying primer based on bitumen, solvents and adhesion-improving additives. Impregnation to ensure good adhesion to the substrate (concrete, metal and wood) before welding (torch-on or hot-air method) or gluing bituminous waterproofing membranes. It is also suitable on old/weathered bituminous waterproofing membranes with a slate or granulate finish.

Characteristics

Composition	bitumen, solvents and adhesion-improving additives
Curing time *	30 min.
Consumption (l/m ²)	0,15 - 0,25
Application temperature (°C)	min. +5

* Depending on conditions (temperature, relative humidity, layer thickness, ...)

Packing & storage

Cans of 5 and 25 l

12 months in original unopened packaging. Store cool, dry, frost-free and protected from sunlight.

Installation

Thoroughly mix the product before use.
Apply with a brush, roller or rubber squeegee on a dry, dust- and grease free substrate.
Allow to dry completely before applying the membrane.
See label for more information.

Cleaning tools:

- wet product: White Spirit

Certifications



Special indications

Hygiene, Health and Environment

For more information, please refer to the relevant safety data sheet.

Quality-, Environment- and Safety Management

SOPREMA always recognises as a high level of importance the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.

SOPREMA reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order.

Contact: www.soprema.com