

ELASTOCOL 500 TP

Description

Cold applied primer based on elastomer bitumen and volatile solvents.

Impregnation to ensure good adhesion to the substrate (concrete, metal and wood) before welding (torch-on or hot-air method) elastomer bitumen based waterproofing membranes.

It is recommended in the waterproofing of civil engineering (for ex. bridge decks and car parks) before welding (torch-on or hot-air method) elastomer bitumen based waterproofing membranes from the CIVIL ROCK range.

Torch-on or hot-air method

Characteristics

	ELASTOCOL 500 TP
Composition	elastomer bitumen and solvents
Curing time *	2 - 12 h
Consumption (l/m ²)	0,15 - 0,25
Application temperature (°C)	min. 0

* Depending on conditions (temperature, relative humidity, layer thickness, ...)

Packing & storage

Cans of 30 L.

12 months in original unopened packaging. Store cool, dry and frost-free.

Installation

Apply with a brush, roller or rubber squeegee on a dry, dust- and grease free substrate.

Allow to dry completely before applying the membrane.

See label for more information.

Cleaning tools:

White Spirit

Special indications

Hygiene, Health and Environment

The membrane does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.
For more information, please refer to the relevant safety data sheet.

Quality-, Environment- and Safety Management

SOPREMA always recognises as a high level of importance the quality of the products, the environment and safety.

For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.



Marnix DERKS
Technical Director
Grobbendonk, 23/03/2018