

EASY TORCH

Description

Membrane composed of polymer bitumen and a fiberglass reinforcement.
Used as an under layer within a multi layer waterproofing system or as a vapour control layer.
The upper surface is finished with talcum/sand with a line at 75 mm at one side.
The lower surface is protected by a thermofusible film.

Composition

	EASY TORCH
Reinforcement	fiberglass
Finish upper side	talcum/sand
Finish lower side	thermofusible film
Coating mass	polymer bitumen

Packing

	EASY TORCH
Dimensions of the roll (m)	10 x 1
Mass of the roll (kg)	33
Number of rolls per pallet	36

Characteristics

		EASY TORCH
Membrane thickness (mm) (EN 1849-1)	MDV	2,5
Membrane mass (kg) (EN 1849-1) (indicative)	MDV	3,3
Tensile force L (N/5cm) (EN 12311-1)	MDV	350
Tensile force T (N/5cm) (EN 12311-1)	MDV	200
Elongation at maximum tensile force L (%) (EN 12311-1)	MDV	NPD
Elongation at maximum tensile force T (%) (EN 12311-1)	MDV	NPD
Dimensional stability (%) (EN 1107-1)	MLV	NPD
Resistance to tearing (nail shank) L (N) (EN 12310-1)	MDV	NPD
Resistance to tearing (nail shank) T (N) (EN 12310-1)	MDV	NPD
Flexibility at low temperature (°C) (EN 1109)	MLV	-5
Flow resistance at elevated temperature (°C) (EN 1110)	MLV	100
Water vapour diffusion-equivalent (m) (EN 1931)	MDV	125

MDV = manufacturer declared value / MLV = manufacturer limiting value / NPD = no performance determined



SOPREMA

Bituminous waterproofing

TECHNICAL DATASHEET



BETF-WPBBE0314.b/EN
cancels and replaces
BETF-WPBBE0314.a/EN

Installation

- Torch-on or hot-air method including the overlaps.
- Loose-laid in a system with heavy surface protection, overlaps torched.

Certifications



No.: **0749**
Standard: **EN 13707 / EN 13970**
Year: **2013**

Special indications

Hygiene, Health and Environment

The membrane does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.
For more information, please refer to the relevant safety data sheet.

Quality-, Environment- and Safety Management

SOPREMA always recognises as a high level of importance the quality of the products, the environment and safety.

For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.



Marnix DERKS
Technical Director
Grobendonk, 27/03/2018

SOPREMA reserves the right to amend the composition of its material and consequently their prices, without prior notice. For this reason, all orders will be accepted only in accordance with the conditions and technical specifications in force at the date of order.

Contact: www.Soprema.com

SOPREMA
GROUP