

GEOTEXTILE FLAG PET TT-300

Description

GEOTEXTILE FLAG PET TT-300 is a non-woven needle punched and thermo-treated polyester fleece.
GEOTEXTILE FLAG PET TT-300 can be used as a compression-, separation- or protection layer on most supports.

Characteristics

Composition	Standard	Unit	Value	Tolerance
Composition			non-woven polyester	
Mass		g/m ²	300	
Technical characteristics				
Thickness membrane at 2 kPa	EN 9863-1	mm	2,30	± 15 %
Tensile force (L / T)	EN 10319	kN/m	5,23 / 6,10	± 15 %
Elongation at rupture (L / T)	EN 10319	%	40 / 50	± 15 %
Resistance to static puncture	EN 12236	N	1000	-10/+0 %
Resistance to impact	EN 13433	mm	25	+20 %
Packing				
Dimensions of the roll		m	≥ 2,20 x 75	
Mass/roll		kg	± 50	

NPD = no performance determined

GEOTEXTILE FLAG PET TT-300 is rot and bitumen resistant and has a high resistance against bacterial deterioration.

Store in a horizontal position in a dry place, protected against moisture and sunlight.

Installation

See installation guidelines of the application.

To prevent deterioration it needs to be completely covered after installation (It can't be applied when permanently exposed to UV radiation).

Special indications

Hygiene, Health and Environment

The product does not contain any substance which is likely to be detrimental to your health or to the environment and complies with generally admitted Health and Safety Requirements.

Quality-, Environment- and Safety Management

SOPREMA always recognises as a high level of importance the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.