

SOPRAMASTIC 200

SOPRAMASTIC 200 is a joint sealant, non crosslinkable, rubber-based plasticized synthetic bitumen.

User application

SOPRAMASTIC 200 is used as complement for bitumen waterproofing membranes as jointing mastic, caulking material or joint filler. It is compatible with bituminous materials and ensures a good waterproofing.

SOPRAMASTIC 200 has been formulated with a high level of polymer in order to resist to flow at high temperatures. Furthermore, it is easy to manipulate at temperature down to 5°C.

Characteristics

	SOPRAMASTIC 200
Colour	Black
Odour	Hydrocarbon
Density at 20°C	1,10 ± 0,50 g/cm ³
Flow	None at temperatures of use
Temperature resistance	-20°C to +80°C
Application temperature range	+5°C to +35°C
Cone penetration at 25°C	175 ± 25 1/10 mm
Flash point (ASTM D 56)	27°C

Setting time between 4 and 24 hours depending on temperature and quantity applied.

Packaging

	SOPRAMASTIC 200
Packaging	Cartridges : 310 ml Barrels : 200 l
Storage	2 years in original can, in a cool, well-ventilated area. Temperature must be kept between +5°C and +20°C. The

Installation

SOPRAMASTIC 200 has an excellent adherence on most materials without primer on clean and free of dust.

310 ml cartridges can be used with a standard cartridge extruder. Apply with a trowel, a brush or a squeegee.

Cleaning tools:

Petroleum solvent (white spirit for example).

Special indications

Hygiene, health and environment:

- Flammable: keep away from flames and sparks during use.
- Do not smoke while product is being used.
- Store product in a cool, ventilated area, away from sunlight.
- Ensure that container is well closed after use.
- If flame is to be used, ensure that all the container, empty or full, are kept at a safe distance of 10 m away.

The product does not contain any substance likely to be detrimental to health or to environment and complies with generally admitted Health and Safety Requirements.

For further information, please refer to relevant Safety Data Sheet.

Quality control:

SOPREMA has always attached the highest importance to the quality of its products, to the respect of environment and men.

For this reason, we apply an integrated management of the Quality and Environment certified **ISO 9001** and **ISO 14001**.