



SOPREMA

DECLARATION OF PERFORMANCE
n° PROFR0027



1 – *Unique identification code of the product-type:*

PROFR0027

Commercial name (s):

STRATEC II S

2 – *Intended use(es):*

Underlays for discontinuous roofing

Underlays for walls

3 – *Manufacturer:*

SOPREMA SAS
15, rue de Saint-Nazaire
67100 STRASBOURG
www.soprema.com

4 – *Authorised representative:*

Non applicable

5 – *System(s) of assessment and verification of constancy of performance:*

AVCP 3

6a – *Harmonised standard:*

EN 13859-1:2010

EN 13859-2:2010

Notified body(ies):

ITC (Notified Body n°1023)

IMBIGS (Notified Body n°1454)

*7 – Declared performance(s):*

Essential characteristics	Performances	Harmonised Technical Specification
Reaction to fire	E	EN 13859-1:2010 EN 13859-2:2010
Resistance to water penetration	W1	
Tensile properties: Tensile strength - Longitudinal - Transversal	350 ± 60 N/50 mm 210 [-10;+60] N/50 mm	
Elongation - Longitudinal - Transversal	100 ± 60% 125 ± 75%	
Resistance to tearing (Nail shank) - Longitudinal - Transversal	190 ± 40 N 225 ± 65 N	
Flexibility at low temperature (Pliability)	-40°C	
Artificial ageing behavior: (1000 h UV + 90 days at 70°C) for: Resistance to water penetration	W1	
Tensile strength - Longitudinal - Transversal	310 ± 75 N/50 mm 180 ± 40 N/50 mm	
Elongation - Longitudinal - Transversal	45 ± 15% 60 ± 25%	
Water vapour transmission properties (Sd)	0.02 [-0.005 ; +0.02] m	

The performances of the product identified above is in conformity with the set of declared performance (s). This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Strasbourg, 9th February 2024,
Export Technical Manager, Mr Pascal MOUGEOT-LUDIN