

Technical Data Sheet MISIT0102.b  
Cancels and replaces MISIT0102.a

## PRODUCT INFORMATION

### DESCRIPTION

Adhesive produced on elastomeric base in a solvent based solution, single-component, liquid with low viscosity, resistant to water.

### USE

The adhesive FLEXOCOL V is used for bonding of PVC waterproofing membranes on vertical surface.

### APPLICATION METHOD

- The supports must be clean and without inconsistent elements on the surface.
- The adhesive FLEXOCOL V must be spread and levelled using a toothed brush or roll or another similar tool applied on the whole surface of the two layers to be glued (PVC membrane + support).
- After verifying the status of stickiness, couple the two layers exerting on them a pressure by metal or rubber roll.
- The setting of the adhesive is immediate while maximum adhesive level is obtained within few days.
- The laying tools can be cleaned with acetone or methylethylketene.

### SPECIFIC INSTRUCTIONS

- Do not use for bonding on polystyrene, on bituminous membranes or other support not compatible for contact with solvents.
- Do not apply on wet support.
- With a temperature below 10 ° C facilitate the evaporation of the solvent using hot air.

### CONSUMPTION

Minimum consumption is of about 500 gr/mq to be applied on the whole surface of the two layers to be glued. The quantities are always purely indicative and should be evaluated considering the specific situation that may be encountered on jobsite

### CHARACTERISTIC

Refer to the Safety Data Sheet.

## STORAGE AND PACKAGING

Shelf-Life	The shelf-life is at least 12 months from production date printed on the packaging, provided that the same is stored in a dry place and in original sealed and undamaged container.
Storage conditions	Store in a dry place at temperatures between +10°C and +30°C
Packaging	5 litres, 10 litres or 20 litres

### NOTES

For further information contact the technical department of Soprema srl.

UNI EN ISO 9001 (Quality Company System) and UNI EN ISO 14001 (Environmental System) certified quality system.

The data herewith indicated are not exhaustive and Soprema srl may modify them without previous notice. Soprema srl, has the right to modify the product at any time and without previous notice, in any of its aspect, and to stop its production. In case of dispute the official version of this sheet product information will be provided directly by the technical office Soprema srl stamped and signed by the technical manager. Soprema srl reserves the right, as technology and know-how progress, to modify without warning the composition and conditions of use of its materials, and subsequently their price. As a result, orders shall only be accepted on the basis of the terms and technical specifications applicable at the time of receipt.