



DECLARATION OF PERFORMANCE

in accordance with Annex III of Regulation (EU) Nr 305/2011 (Construction Products Regulation):

SOPRAVAP ALU Activa 2

Number: **DOP_WPBDE280**

Version: **b/EN**

1. Unique identification code of the product-type:
EN 13970
2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
SOPRAVAP ALU Activa 2
3. Intended use(s) of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:
Bitumen water vapour control layer
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
SOPREMA GmbH
Mammutfeld 1
56479 Oberroßbach
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):
not applicable
6. System(s) of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 3
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
Notified body:
Kiwa GmbH
Polymer Institut
Quellenstraße 3
65439 Flörsheim-Wicker
Germany

has performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity 1119 - CPR – 14151 of the factory production control

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
not applicable

9. Declared performances SOPRAVAP ALU Activa 2


Essential characteristics	Performances	Harmonised technical specification
Reaction to fire	E	EN 13970:2004+A1:2006
Watertightness method B	Conform	
Tensile properties:: Maximal tensile force longitudinal (N/50 mm)	≥600	
Maximal tensile force transversal (N/50 mm)	≥600	
Elongation at maximal tensile force longitudinal (%)	≥2,5	
Elongation at maximal tensile force transversal (%)	≥2,5	
Resistance to impact method A (mm) or resistance to impact method A and B (mm)	300 NPD	
Shear resistance of joints l/t (N/50 mm)	≥600/≥400	
Flexibility at low temperature (°C)	≤ -20	
Resistance to tearing (nail shank) (N)	NPD	
Durability μ	NPD	
Water vapour permeability sd (m)	≥1.500	
Dangerous substances ^{a), b)}	Meets requirement, see 5.14 EN 13970	

- a) this product does not contain asbestos or tar constituents
b) in the absence of European harmonized test methods on leaching behaviour, no statement can be made.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Mannheim, 25.06.2018

Wolfgang Clotten



Technical Director