

ALSAN MASTIC 2200

Description

Flexible mastic based on bitumen and synthetic rubber.
Used for sealing small tears, cracks, joints and local repairs.

Characteristics

Composition	bitumen and synthetic rubber
Temperature resistance	-20/+80 °C
Application temperature	+5 / +35 °C
Consumption	15-20 m/cartridge

Packing & storage

Cartridge 310 ml
20 cartridges/box

Minimum 12 months in original unopened packaging, stored in a dry and cool place, protected from sunlight at a temperature between +10 and +25 °C.

Installation

ALSAN MASTIC 2200 is applied with a gun on a clean and dust-free surface.
It has excellent adhesion to most materials without prior treatment with a primer.
It can be applied on a slightly damp surface.
Apply **ALSAN MASTIC 2200** so that it is in full contact and has good adhesion to the edges of the joint.
The curing time is 4 to 24 hours depending on the conditions and dimensions of the joint.

Cleaning tools:

White Spirit

Special indications

Hygiene, Health and Environment

For more information, please refer to the relevant safety data sheet.

Quality-, Environment- and Safety Management

SOPREMA always recognises as a high level of importance the quality of the products, the environment and safety.
For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with **EN ISO 9001** and **EN ISO 14001**.